

**ACCESORIO INOXIDABLE PARA SOLDAR  
PRODUCTO SCH10, CALIDAD ASTM A403**  
**APLICACIONES:** gas natural, industria alimentaria, entornos industriales y temperaturas extremas, conducción de fluidos, calderas.



CODIGO A304L	P.V.P €	DN	D mm	T mm	M mm	C mm
TS15	4,41	½"	21.34	2.11	25.40	25.40
TS20	4,96	¾"	26.67	2.11	28.70	28.70
TS25	7,58	1"	33.40	2.77	38.10	38.10
TS32	9,21	1¼"	42.16	2.77	47.75	47.75
TS40	10,10	1½"	48.26	2.77	57.15	57.15
TS50	12,07	2"	60.32	2.77	63.50	63.50
TS65	19,66	2½"	73.02	3.05	76.20	76.20
TS80	24,76	3"	88.90	3.05	85.85	85.85
TS100	38,37	4"	114.30	3.05	104.90	104.90
TS125	70,00	5"	141.30	3.40	123.95	123.95
TS150	9,85	6"	168.27	3.40	143.00	143.00



CODIGO A304L	P.V.P €	DN	D mm	T mm	H mm
CAP15	4,37	½"	21.34	2.11	25.40
CAP20	4.84	¾"	26.67	2.11	25.40
CAP25	2.70	1"	33.40	2.77	38.10
CAP32	3.45	1¼"	42.16	2.77	38.10
CAP40	3.40	1½"	48.26	2.77	38.10
CAP50	4.79	2"	60.32	2.77	38.10
CAP65	6.46	2½"	73.02	3.05	38.10
CAP80	8.97	3"	88.90	3.05	50.80
CAP100	12.90	4"	114.30	3.05	63.50
CAP125	23.99	5"	141.30	3.40	76.20
CAP150	29.37	6"	168.27	3.40	88.90